



Gallagher Security (Europe) Limited

FT 1600 SE



Category: Detection Systems

Sub Category: Barrier Mounted Detection

Description

The system has been assessed on a 50 metre section of 3 metre high palisade fence.



Manufacturer

Manufacturer Name:	Gallagher Security (Europe) Limited
--------------------	-------------------------------------

Country:	United Kingdom
----------	----------------

Post Code:	CV34 6XZ
------------	----------

Address Line 1:	Tournament Fields Agincourt Road
-----------------	----------------------------------

Address Line 2:	Warwick
-----------------	---------

State/County:	Warwickshire
---------------	--------------

Telephone:	024 76641234
------------	--------------

Fax:	02476 641235
------	--------------

Website:	https://security.gallagher.com/
----------	---

Email:	ukhighsecurity@gallagher.com
--------	--

Specification

The approved electrified fence has the following configuration:

On the protected side the wires will be spaced at 60mm for the bottom 1.8m and continue to the top of the physical fence at a spacing of 91mm.

The system topping shall be attack facing and extend a minimum of 1.6m above the physical fence. The wires will be spaced at 91mm (60mm for the top 3 wires) and overlap the top of the physical structure by a minimum of 3



wires.

There shall be one additional 1.7m high dropper post (28 wires) between the fence intermediate posts. Alternate insulators are to be secured with the Gallagher security pin to a height of 1.5m and for the top 3 wires.

The height of the Gallagher FT 1600SE shall be the height of the host fence plus a minimum of 1.6m acting to form a topping.

For example a 3.0m high host fence would require a minimum 4.6m electrified system.

The host fence strength, (including foundations), must be suitable to provide support for a tension-wire system
